

**TITLE**

**APPARATUS AND METHOD FOR OPERATING AND MAINTAINING  
PRIVATE MOBILE COMMUNICATION SERVICE SYSTEM  
USING IP NETWORK**

**CLAIM OF PRIORITY**

**[0001]** This application makes reference to, incorporates the same herein, and claims all benefits accruing under 35 U.S.C. §119 from an application entitled "*APPARATUS AND METHOD FOR OPERATING AND MAINTAINING PRIVATE MOBILE COMMUNICATION SERVICE SYSTEM USING IP NETWORK*" earlier filed in the Korean Intellectual Property Office on 11 February 2003 and thereby duly assigned Serial No. 2003-8633.

**BACKGROUND OF THE INVENTION**

**Technical Field**

**[0002]** The present invention relates generally to an apparatus and method for operating and maintaining a private mobile communication service system using an Internet Protocol network and, more particularly, to an apparatus and method for operating and maintaining a private mobile communication service system using an Internet Protocol network, which is capable of processing operation/maintenance information between the wireless system manager of the private mobile communication service system and the base station controller main processor of a private base station transceiver subsystem in the private mobile communication service system using a local area network.

**Related Art**

**[0003]** Generally, a private wired communication service for voice within a local area is provided through a private branch exchange (PBX) or key phone system, and a communication service for data within a local area is provided through a local area network (LAN) switch and a router using a server.

**[0004]** Further, generally, a mobile communication service can be provided anywhere beyond a limited area, such as a local area. However, such a mobile communication service is provided using a mobile communication service system, and is not constructed to allow a wireless communication to be performed without charge within a specific area.

**[0005]** That is, in order for a terminal of a wired PBX and a mobile terminal of a subscriber to the mobile communication service to communicate with each other, a corresponding terminal is connected to a public network through the exchange thereof, and a call from the terminal is linked to the other.

**[0006]** In this case, the public network includes a mobile communication network and a public switched telephone network (PSTN). Therefore, there is an inconvenience in that, even though a wired communication service subscriber and a mobile communication service subscriber communicate with each other by phone within the same building, a fee is charged for the call.

**[0007]** Therefore, there has been developed a private mobile communication service system which enables telephonic communication without charge when a wired communication service subscriber and a mobile communication service subscriber make a call within the same building (in this case, a mobile communication service system is referred to as a “public mobile

1 communication service system” so as to be differentiated from a private mobile communication  
2 service system).

3 **[0008]** The developed private mobile communication service system enables a mobile  
4 communication service subscriber registered with the private mobile communication service to be  
5 provided with call service between the subscriber and another subscriber registered with the  
6 private mobile communication service, or with a subscriber of an extension telephone connected  
7 to a PBX, without charge within an area in which the private mobile communication service is  
8 provided.

9 **[0009]** To provide both the public and private mobile communication services, a service system  
10 includes a public/private common cell area, which is a common service area shared between public  
11 and private communication services, and a public/private communication service apparatus.

12 **[0010]** In order to differentiate base station transceiver subsystems (BTSs) belonging to a public  
13 mobile communication service system, (as an example) from a private BTS belonging to the  
14 public/private common cell area, the private BTS is referred to as a “pBTS.”

15 **[0011]** The pBTS functions to establish a radio communication channel with a mobile station  
16 (MS) belonging to the public/private common cell area, and manage radio resources. Further, the  
17 pBTS is connected (for example) to a base station controller (BSC) of the public mobile  
18 communication service system through the public/private communication service apparatus.

19 **[0012]** The public/private communication service apparatus is connected to the BSC of the  
20 public mobile communication service system, a public switched telephone network/integrated  
21 services digital network (PSTN/ISDN), and an internet protocol (IP) network. The public/private

1 communication service apparatus provides a mobile communication service so that public and  
2 private mobile communication services are selectively provided to mobile stations in the  
3 public/private common cell area, for example.

4 **[0013]** If the mobile station is registered with the public/private communication service  
5 apparatus so as to be capable of being provided with the private mobile communication service,  
6 the mobile station can be provided with the private mobile communication service as well as the  
7 public mobile communication service.

8 **[0014]** However, if the mobile station is not registered with the public/private communication  
9 service apparatus so as to be provided with the private mobile communication service, the mobile  
10 station can only be provided with the public mobile communication service. Further, the  
11 public/private communication service apparatus also provides a wired communication service in  
12 conjunction with the PSTN/ISDN and the IP network.

13 **[0015]** The public mobile communication service system is configured so that a BTS and a BSC  
14 are separately located and transmit and receive necessary signals to and from each other, whereas  
15 the private mobile communication service system is configured so that pBTS and pBSC are located  
16 at the same place side by side.

17 **[0016]** Further, a maintenance and administration personal computer (MAP), used when an  
18 operator operates and maintains a pBSC, is connected to the pBSC or pBTS through a LAN so that  
19 the operator can easily be made aware of the status of the pBSC and pBTS, thus being capable of  
20 easily operating and maintaining the private mobile communication service system.

21 **[0017]** Moreover, a call manager that controls the radio calls of the private mobile

1 communication service system is connected to the pBSC and the pBTS through the LAN, and  
2 functions to operate and manage the radio resources of the pBSC and pBTS.

3 **[0018]** The call manager is provided with a wireless system manager (WSM) that performs an  
4 operation/maintenance function for the pBSC, such as loading, configuration management,  
5 statistics measurement, status monitoring, failure control and system tests. The WSM exchanges  
6 operation/maintenance information with the pBSC through an optical cable.

7 **[0019]** That is, by providing the call manager and the pBSC with respective optical transceivers,  
8 and connecting the optical transceivers with an optical cable, the pBSC and the WSM of the call  
9 manager can exchange operation/maintenance information with each other.

10 **[0020]** Meanwhile, the pBSC employs a BSC asymmetric transfer mode (ATM) switch network  
11 (BAN), which is an ATM switch having a capacity of 2.5 Gbps, to transmit the  
12 operation/maintenance information to the WSM of the call manager. The pBSC converts the  
13 operation/maintenance information transmitted from the BSC main processor (BMP) of the pBSC  
14 into ATM data through the BAN, and transmits the ATM data to the WSM of the call manager  
15 through the optical transceivers and the optical cable.

16 **[0021]** The BAN includes an ATM cell mux/demux board assembly (ACMA) board for  
17 multiplexing/demultiplexing ATM cells, an ATM switch fabric board assembly (ASFA) board for  
18 providing communication paths between the BMP and other processors, an ATM E1/T1 interface  
19 board assembly (AETA) board connected to the pBTS through an E1/T1 link to exchange ATM  
20 cells with the pBTS, and an ATM STM-1 interface board assembly (AS1A) board matched to one  
21 port of the ASFA board in a ratio of 1:1 to transmit and receive data to and from the WSM of the

1 call manager through low voltage differential signaling (LVDS).

2 [0022] The pBSC transmits the data operation/maintenance information, which is received from  
3 the BSM, to the WSM of the call manager through the DAMA board, the ASFA board and the  
4 AS1A board through the optical cable.

5 [0023] As described above, the physical connection between the WSM and BMP is  
6 accomplished based upon ATM. The BMP of the pBSC is connected to an ATM interface card  
7 and the optical cable through the ASFA board and the AI1A board of the BAN positioned in the  
8 WSM. However, it can be appreciated that traffic exchanged between the BMP and the WSM is  
9 data related to operation/maintenance, and is not time-dependent traffic that requires a guarantee  
10 of quality of service (QoS).

11 [0024] Accordingly, it is not necessary for the WSM and the BMP to perform ATM  
12 communication based on an expensive ATM network to handle such network traffic.

13 [0025] The following patents are considered to be generally pertinent to the present invention,  
14 but are burdened by the disadvantages set forth above:

15 U.S. Patent No. 6,628,965 to LaRosa *et al.*, entitled *COMPUTER METHOD AND SYSTEM FOR*  
16 *MANAGEMENT AND CONTROL OF WIRELESS DEVICES*, issued on September 30, 2003; U.S.  
17 Patent No. 6,570,871 to Schneider, entitled *INTERNET TELEPHONE SERVICE USING*  
18 *CELLULAR DIGITAL VOCODER*, issued on May 27, 2003; U.S. Patent No. 6,542,497 to Curry  
19 *et al.*, entitled *PUBLIC WIRELESS/CORDLESS INTERNET GATEWAY*, issued on April 1, 2003;  
20 U.S. Patent No. 6,493,328 to Fong *et al.*, entitled *ACTIVE SET MANAGEMENT IN CELLULAR*  
21 *WIRELESS NETWORK THAT SUPPORTS HIGH DATA RATE FORWARD LINK*

1 *TRANSMISSIONS*, issued on December 10, 2002; U.S. Patent No. 6,466,571 to Dynarski *et al.*,  
2 entitled *RADIUS-BASED MOBILE INTERNET PROTOCOL (IP) ADDRESS-TO-MOBILE*  
3 *IDENTIFICATION NUMBER MAPPING FOR WIRELESS COMMUNICATION*, issued on  
4 October 15, 2002; U.S. Patent No. 6,421,714 to Rai *et al.*, entitled *EFFICIENT MOBILITY*  
5 *MANAGEMENT SCHEME FOR A WIRELESS INTERNET ACCESS SYSTEM*, issued on July 16,  
6 2002; U.S. Patent No. 6,418,324 to Doviak *et al.*, entitled *APPARATUS AND METHOD FOR*  
7 *TRANSPARENT WIRELESS COMMUNICATION BETWEEN A REMOTE DEVICE AND HOST*  
8 *SYSTEM*, issued on July 9, 2002; U.S. Patent No. 6,374,078 to Williams *et al.*, entitled *WIRELESS*  
9 *COMMUNICATION SYSTEM WITH MULTIPLE EXTERNAL COMMUNICATION LINKS*, issued  
10 on April 16, 2002; U.S. Patent No. 6,272,129 to Dynarski *et al.*, entitled *DYNAMIC ALLOCATION*  
11 *OF WIRELESS MOBILE NODES OVER AN INTERNET PROTOCOL (IP) NETWORK*, issued on  
12 August 7, 2001; U.S. Patent No. 6,075,783 to Voit, entitled *INTERNET PHONE TO PSTN*  
13 *CELLULAR/PCS SYSTEM*, issued on June 13, 2000; U.S. Patent No. 6,014,429 to LaPorta *et al.*,  
14 entitled *TWO-WAY WIRELESS MESSAGING SYSTEM WITH TRANSACTION SERVER*, issued  
15 on January 11, 2000; U.S. Patent No. 5,974,300 to LaPorta *et al.*, entitled *TWO-WAY WIRELESS*  
16 *CELLULAR MESSAGING SYSTEM*, issued on October 26, 1999; and U.S. Patent No. 6,560,222  
17 to Pounds *et al.*, entitled *SYSTEMS AND METHODS FOR MULTIPLE VOICE AND DATA*  
18 *COMMUNICATIONS USING INTELLIGENTLY BRIDGED TDM AND PACKET BUSES AND*  
19 *METHODS FOR PERFORMING TELEPHONY AND DATA FUNCTIONS USING THE SAME*,  
20 issued on May 6, 2003.

**SUMMARY OF THE INVENTION**

**[0026]** Accordingly, the present invention has been developed while keeping in mind the above problems occurring in the prior art, and an object of the present invention is to provide a system and method for operating and maintaining a private mobile communication service system using an IP network, in which system the ATM data communication performed between a WSM and a BMP, and based upon an ATM network, is replaced with LAN communication based upon Fast Ethernet, thus reducing the cost of the installation and of use of the WSM system, and improving flexibility.

**[0027]** In order to accomplish the above object, the present invention provides an apparatus for operating and maintaining a private mobile communication service system using an IP network, the private mobile communication service network having a pBSC and a BTS, the apparatus including: a WSM for receiving operation/maintenance information from the pBSC through the IP network, for processing the operation/maintenance information, for creating an operation/maintenance control signal, and for transmitting the operation/maintenance control signal to the pBSC through the IP network; a hardware alarm collection unit mounted on the pBSC for collecting operation/ maintenance information from each of a plurality of boards, for outputting the operation/maintenance information, for receiving an operation/maintenance control signal from each board, and for generating a reset signal for each board; and a BMP responsive to the operation/maintenance information being received from the hardware alarm collection unit for ascertaining a link address and transmitting the operation/maintenance information if the link address is the WSM, and responsive to the operation/maintenance control signal being received



1 from the WSM through the IP network for transmitting the operation/maintenance control signal  
2 to the hardware alarm connecting unit.

3 **[0028]** In accordance with another embodiment of the present invention, there is provided a  
4 method of operating and maintaining a private mobile communication service system using an IP  
5 network, the private mobile communication service network having a pBSC and a BTS, the  
6 method including the steps of: ascertaining, via a BMP, a link address of operation/maintenance  
7 information of each of a plurality of boards collected by a hardware alarm collection unit; when  
8 the link address is a WSM as ascertained in the first step, transmitting, via the BMP, the  
9 operation/maintenance information to the WSM through the IP network for processing of the  
10 operation/maintenance information by the WSM; creating, via the WSM, an  
11 operation/maintenance control signal, and transmitting the operation/maintenance control signal  
12 to the BMP through the IP network; and receiving, at the BMP, the operation/maintenance control  
13 signal, and transmitting the operation/maintenance control signal to the hardware alarm collection  
14 unit, the hardware alarm collection unit creating and outputting a reset signal for each of the  
15 respective boards.

#### 16 **BRIEF DESCRIPTION OF THE DRAWINGS**

17 **[0029]** A more complete appreciation of the invention, and many of the attendant advantages  
18 thereof, will be readily apparent as the same becomes better understood by reference to the  
19 following detailed description when considered in conjunction with the accompanying drawings  
20 in which like reference symbols indicate the same or similar components, wherein:

1     **[0030]**   FIG. 1 is a diagram of a network structure illustrating the concept of public and private  
2     mobile communication services;

3     **[0031]**   FIG. 2 is a configuration diagram of a private mobile communication service system;

4     **[0032]**   FIG. 3 is a diagram showing an example of an optical cable for providing connection  
5     between a call manager and a pBSC;

6     **[0033]**   FIG. 4 is a configuration diagram of an apparatus for operating and maintaining a private  
7     mobile communication service system using a LAN in accordance with an embodiment of the  
8     present invention;

9     **[0034]**   FIG. 5 is a configuration diagram of a BHPA board for the BMP of FIG. 4;

10    **[0035]**   FIG. 6 is a configuration diagram of the WSM of FIG. 4;

11    **[0036]**   FIG. 7 is a flowchart of the processing of operation/maintenance information in the  
12    private mobile communication service system using the LAN in accordance with an embodiment  
13    of the present invention; and

14    **[0037]**   FIG. 8 is a flowchart of the processing of an operation/maintenance control signal in the  
15    private mobile communication service system using the LAN in accordance with an embodiment  
16    of the present invention

## 17                   **DESCRIPTION OF THE PREFERRED EMBODIMENTS**

18    **[0038]**   Reference now should be made to the drawings, in which the same reference numerals  
19    are used throughout the different drawings to designate the same or similar components.

20    **[0039]**   FIG. 1 is a diagram of a network structure illustrating the concept of public and private

1 mobile communication services.

2 **[0040]** As shown in FIG. 1, to provide both the public and private mobile communication  
3 services, a service system includes a public/private common cell area 114, which is a common  
4 service area shared between public and private communication services, and a public/private  
5 communication service apparatus 112.

6 **[0041]** In order to differentiate base station transceiver subsystems (BTSs) belonging to a public  
7 mobile communication service system 115 (that is, BTSs 106-1 to 106-k and 108-1 shown in FIG.  
8 1 as examples) from a private BTS 108-k belonging to the public/private common cell area 114,  
9 the private BTS 108-k is referred to as a “pBTS.”

10 **[0042]** The pBTS 108-k functions to establish a radio communication channel with a mobile  
11 station (MS) 124 belonging to the public/private common cell area 114, and manage radio  
12 resources. Further, the pBTS 108-k is connected to a base station controller (BSC) of the public  
13 mobile communication service system (for example, the BSC 104-m shown in FIG. 1) through the  
14 public/private communication service apparatus 112.

15 **[0043]** The public/private communication service apparatus 112 is connected to the BSC 104-m  
16 of the public mobile communication service system, a public switched telephone network  
17 /integrated services digital network (PSTN/ISDN) 116, and an internet protocol (IP) network 118.  
18 The public/private communication service apparatus 112 provides a mobile communication service  
19 so that public and private mobile communication services are selectively provided to MSs in the  
20 public/private common cell area 114 (for example, the MS 124 of FIG. 1).

21 **[0044]** If the MS 124 is registered with the public/private communication service apparatus 112

1 so as to be capable of being provided with private mobile communication service, the MS 124 can  
2 be provided with the private mobile communication service as well as the public mobile  
3 communication service.

4 **[0045]** However, if the MS 124 is not registered with the public/private communication service  
5 apparatus 112 so as to be provided with private mobile communication service, the MS 124 can  
6 only be provided with public mobile communication service. Further, the public/private  
7 communication service apparatus 112 also provides wired communication service in conjunction  
8 with the PSTN/ISDN 116 and the IP network 118.

9 **[0046]** FIG. 2 is a configuration diagram of a private mobile communication service system.  
10 The public mobile communication service system is configured so that a BTS and a BSC are  
11 separately located, and transmit and receive necessary signals to and from each other, whereas the  
12 private mobile communication service system is configured so that a pBTS 232 and pBSC 230 are  
13 located at the same place side by side.

14 **[0047]** Further, a maintenance and administration personal computer (MAP) 220, used when  
15 an operator operates and maintains a pBSC, is connected to the pBSC 230 or pBTS 232 through  
16 a LAN so that the operator can easily be made aware of the status of the pBSC 230 and pBTS 232,  
17 thus being capable of easily operating and maintaining the private mobile communication service  
18 system.

19 **[0048]** Further, a call manager 210 for controlling the radio calls of the private mobile  
20 communication service system is connected to the pBSC 230 and the pBTS 232 through the LAN,  
21 and functions to operate and manage the radio resources of the pBSC 230 and pBTS 232.

1   **[0049]**   The call manager 210 is provided with a wireless system manager (WSM) that performs  
2   an operation/maintenance function for the pBSC 230, such as loading, configuration management,  
3   statistics measurement, status monitoring, failure control and system tests. The WSM exchanges  
4   operation/maintenance information with the pBSC 230 through an optical cable.

5   **[0050]**   That is, as understood from FIG. 3, by providing the call manager 210 and the pBSC 230  
6   with optical transceivers 310 and 320, respectively, and connecting the optical transceivers 310  
7   and 320 with an optical cable 325, the pBSC 230 and the WSM of the call manager 210 can  
8   exchange operation/maintenance information with each other.

9   **[0051]**   Meanwhile, the pBSC 230 employs a BSC asymmetric transfer mode (ATM) switch  
10   network (BAN), which is an ATM switch having a capacity of 2.5 Gbps, to transmit the  
11   operation/maintenance information to the WSM of the call manager 210. The pBSC 230 converts  
12   the operation/maintenance information, transmitted from the BSC main processor (BMP) of the  
13   pBSC 230, into ATM data through the BAN, and transmits the ATM data to the WSM of the call  
14   manager 210 through the optical transceivers 310 and 320 and the optical cable 325.

15   **[0052]**   The BAN includes an ATM cell mux/demux board assembly (ACMA) board for  
16   multiplexing/demultiplexing ATM cells, an ATM switch fabric board assembly (ASFA) board for  
17   providing communication paths between the BMP and other processors, an ATM E1/T1 interface  
18   board assembly (AETA) board connected to the pBTS through an E1/T1 link to exchange ATM  
19   cells with the pBTS, and an ATM STM-1 interface board Assembly (AS1A) board matched to one  
20   port of the ASFA board in a ratio of 1:1 so as to transmit and receive data to and from the WSM  
21   of the call manager 210 through a low voltage differential signaling (LVDS).

1     **[0053]**   The pBSC 230 transmits the data operation/maintenance information, which is received  
2     from the BSM, to the WSM of the call manager 210 through the DAMA board, the ASFA board  
3     and the AS1A board through the optical cable 325.

4     **[0054]**    As described above, the physical connection between the WSM and BMP is  
5     accomplished based upon an ATM. The BMP of the pBSC 230 is connected to an ATM interface  
6     card and the optical cable 325 through the ASFA board and the A11A board of the BAN positioned  
7     in the WSM. However, it can be appreciated that traffic exchanged between the BMP and the  
8     WSM is data related to operation/maintenance, and is not time-dependent traffic that requires a  
9     guarantee of Quality of Service (QoS).

10    **[0055]**   Accordingly, it is not necessary for the WSM and the BMP to perform ATM  
11    communication based on an expensive ATM network for handling such network traffic.

12    **[0056]**   A preferred embodiment of the present invention is described in detail with reference to  
13    FIGS. 4 to 8 below.

14    **[0057]**   FIG. 4 is a configuration diagram of an apparatus for operating and maintaining a private  
15    mobile communication service system using a LAN in accordance with an embodiment of the  
16    present invention.

17    **[0058]**   Referring to FIG. 4, the apparatus for operating and maintaining a private mobile  
18    communication service system using a LAN in accordance with an embodiment of the present  
19    invention includes an ASFA board 410 provided with an ATM switch fabric to perform ATM  
20    switching, an AETA board 421 connected to a pBSC and a pBTS (pPBX 423) through an E1/T1  
21    link so as to transmit and receive ATM cells, a transcoder control and link assembly (TCLA) board

1 422 for performing a vocoder function and a gateway function for connection with a pPBX, a BSC  
2 high performance processor board assembly (BHPA) for an air termination processor (ATP) 431  
3 that is provided with the ATP for matching with a mobile terminal in a wireless environment, a  
4 BHPA for a BMP 441 that is provided with a BMP for overall control of the pBSC, a hardware  
5 alarm collection board assembly (HACA) board 442 provided with a hardware alarm collecting  
6 block (HAB) for collecting alarm information generated in the respective elements of the pBSC,  
7 ACMA boards 420, 430 and 440 for multiplexing and demultiplexing ATM cells to provide  
8 communication paths between the respective boards 421, 422, 431 and 441 and the ASFA board  
9 410, and a WSM 450 for operating and maintaining the pBSC while transmitting and receiving  
10 operation/maintenance information to and from the BHPA board for a BMP 441 through a Fast  
11 Ethernet link.

12 **[0059]** In this case, the AETA board 421 provides not only a communication path between the  
13 pBSC and the pBTS, but also a communication path between a public BSC 425 and the pBSC 423.

14 **[0060]** In more detail, the AETA board 421 is positioned between the pBTS and the pBSC, and  
15 between the public PBS 425 and the pBSC, and supports exchanges of all data by the BAN,  
16 including an ATM switch and connections between the pBTS and the pBSC, and between the  
17 public PBS 425 and the pBSC through an ATM-E1/T1 link.

18 **[0061]** The AETA board 421 is provided with an E1 interface unit, an ATM layer interface unit  
19 and an interprocessor communication (IPC) unit, is connected to the public BSC 425 and the pBTS  
20 through an E1/T1 link, and transmits and receives ATM cells to and from the public BSC 425 and  
21 the pBTS.

1     **[0062]**   That is, the AETA board 421 transmits ATM cells, received from the public BSC 425  
2     or pBTS, to the BHPA board for a BMP 441 through the ACMA(a) board 440 and the ASFA board  
3     410, or ATM cells, received from the BHPA board for a BMP 441 through the ASFA board 410  
4     and the ACMA(a) board 440, to the public BSC 425 or pBTS. A plurality of AETA boards 421  
5     may be positioned in the pBSC as needed.

6     **[0063]**   Next, the TCLA board 422 functions as a vocoder and a gateway for connecting with the  
7     pPBX 424. The number of the TCLA boards 422 is different, depending upon the extent of calls.

8     **[0064]**   The TCLA board 422 converts subscriber traffic signals, such as 8k/13k QCELP and 8k  
9     EVRC, into a 64k PCM data through digital signal processor (DSP) signals, and vice versa.

10    **[0065]**   The number of DSPs used in the above case is sixteen in each of the TCLA boards 422.  
11    Each of the DSPs can vocode data of eight channels. The TCLA board 422 functions to allow data  
12    to be exchanged between the E1/T1 link and the DSP through a time switch positioned in the  
13    TCLA board 422.

14    **[0066]**   Each of the TCLA boards 422 accommodates a vocoder of 120 channels, provides four  
15    E1s and five T1s, and provides a No. 7 signal channel.

16    **[0067]**   The BHPA board for an ATP 431 functions to process voice and data calls, control  
17    power, perform handoff, and perform MAC control and a radio link protocol (RLP).

18    **[0068]**   The BHPA board for an ATP 431 functions as the air interface of the pBSC, and  
19    transmits and receives ATM cells through the ASFA board 410 and the ACMA 430.

20    **[0069]**   In general, the BHPA board for an ATP 431 includes six to eight boards, which consist  
21    of two BHPA boards for processing traffic data control signals, two BHPA boards for processing



1 circuit data, two BHPA boards for interworking with a public data switching network (PDSN), and  
2 two boards reserved for evolution-data only (EV-DO) in the future.

3 **[0070]** The two BHPA boards for interworking with a PDSN are used in the MAC layer to  
4 transmit and receive packet data across a wireless region.

5 **[0071]** MAC layers are provided in a mobile terminal and the pBSC, respectively, and each  
6 include an RLP entity and a Radio Burst Protocol (RBP) entity.

7 **[0072]** The BHPA board for a BMP 441 is the main control unit of the pBSC and functions to  
8 process the calls of the pBSC and No. 7 signals, manage the resources of the pBSC, and control  
9 an ATM link.

10 **[0073]** The HACA board 442 functions to collect hardware failure information generated by the  
11 respective boards of the pBSC, and to report the collected hardware failure information to the  
12 BHPA board for a BMP 441.

13 **[0074]** In addition, the HACA board 442 functions to generate a reset signal under the control  
14 of the BHPA board for a BMP 441 so as to remotely reset a failed board.

15 **[0075]** The HACA board 442 collects hardware failure information generated in the pBSC  
16 through a cable, transmits the hardware failure information to the BHPA board for a BMP 441, and  
17 employs a 2\*5 hard metric (HM) connector and a 30AWG 5 pair twist cable.

18 **[0076]** The HACA board 442 is connected to a cable through a maximum of 21 ports, and can  
19 collect six pieces of failure information. Accordingly, the HACA board 442 can collect 126 pieces  
20 of hardware failure information.

21 **[0077]** In this case, the failure information is physically a 3.3 V LVT signal, is configured so

1 that a failure is assigned one edge-pin, and employs a single-ended transmission method. The reset  
2 signal accommodated in the 2\*5 cable together with the failure information is a 3.3 V LVT signal,  
3 and contains a synchronizing clock together with reset data to allow a reset to be reliably  
4 performed.

5 **[0078]** The ACMA boards 420, 430 and 440 function to receive data transmitted from the AETA  
6 board 421, the TCLA board 422, the BHPA board for an ATP 431, and the BHPA board for a BMP  
7 441 by the cell, to multiplex the data, and to transmit the data to the ASFA board 410.

8 **[0079]** Additionally, the ACMA boards 420, 430 and 440 function to demultiplex cells  
9 transmitted from the ASFA board 410, to analyze the information of the cell, and to transmit the  
10 information of the cell to the AETA board 421, the BHPA board for an ATP 431, and the BHPA  
11 board for a BMP 441.

12 **[0080]** The ASFA board 410, the BHPA board for a BMP 441 and the ACMA(a) board 440 are  
13 occasionally dualized to improve the reliability of a product. A path of dualization is Fast  
14 Ethernet. The ASFA board 410 notifies a counterpart board of the state of each board to detect the  
15 failure of the board. Since the ASFA board 410, which is an ATM switching board, and the  
16 HACA board 442, which receives an alarm generated in each unit of the pBSC 425, is not provided  
17 with their processors, the BHPA board for a BMP 441 controls the ASFA board 410 through an  
18 Industry Standard Architecture (ISA) to perform an ATM switching operation, and controls the  
19 HACA board 442 through the ISA bus to read the alarm information of each unit.

20 **[0081]** The above-described boards 410, 420, 421, 422, 430, 440, 441 and 442 are mounted on  
21 a shelf backplane (not shown), and exchange various data through shared buses mounted on the

shelf backplane. The shared buses consist of a single 16-bit ATM cell bus for transmitting ATM cells between the boards 410, 420, 421, 422, 430, 440, 441 and 442, an OAM data bus for exchanging various data to perform the operating/maintaining functions of the BHPA board for a BMP 441, and a local bus for transmitting other local data.

**[0082]** The WSM 450 has a completely modular structure in consideration of the operation and maintenance of software, and includes a general function module, an operation function module, a maintenance function module, and an additional function module.

**[0083]** In the meantime, operation information related to the operational function processed by the boards 410, 420, 422, 430, 431 and the maintenance information related to the maintenance function processed by the WSM 450 are collected by the HACA board 442, and reported to the BHPA board for a BMP 441.

**[0084]** When the BHPA board for a BMP 441 receives the operation information or maintenance information from the HACA board 442, the BHPA board for a BMP 441 sends the operation information or maintenance information to the WSM 450 through the Fast Ethernet link.

**[0085]** The BHPA board 441 for a BMP receives the operation information or maintenance information transmitted from the WSM 450 through the FAST Ethernet link, and transmits the operation information or maintenance information so that a failed board or the like is capable of being operated and maintained.

**[0086]** FIG. 5 is a configuration diagram of the BHPA board for a BMP of FIG. 4.

**[0087]** Referring to the drawing, the BHPA board for a BMP 441 includes an operation/maintenance information receiving unit 510 for receiving operation/maintenance

1 information from the HACA board 442, a link address ascertaining unit 520 for ascertaining a link  
2 address, and for transmitting the operation/maintenance information to a LAN interface 530 if the  
3 destination of the operation/maintenance information is the WSM 450, a LAN interface 530 for  
4 providing an interface with a LAN, an operation/maintenance control signal receiving unit 540 for  
5 receiving a control signal for operation/maintenance, an operation/maintenance control signal  
6 transmitting unit 550 for transmitting an operation/maintenance control signal to the HACA board  
7 442, and a memory 560.

8 **[0088]** The operation/maintenance information receiving unit 510 receives the  
9 operation/maintenance information from the HACA board 442, stores the operation/maintenance  
10 information in the memory 510, and transmits the operation/maintenance information to the link  
11 address ascertaining unit 520.

12 **[0089]** Then, the link address ascertaining unit 520 ascertains the destination address of the  
13 operation/maintenance information, and transmits the operation/maintenance information to the  
14 LAN interface 530 if the destination address is the WSM 450, or to the ATM network if the  
15 destination address is not the WSM 450.

16 **[0090]** The LAN interface 530 allows the operation/maintenance information to be transmitted  
17 to the WSM 450 by receiving a frame having a destination address of the WSM 450 and  
18 transmitting the frame to the LAN.

19 **[0091]** Meanwhile, the operation/maintenance control signal created in the WSM 450 is  
20 received by the operation/maintenance control signal receiving unit 540 through the LAN interface  
21 530, and is stored in the memory 560.

1     **[0092]**     Further, the operation/maintenance control signal receiving unit 540 transmits the  
2     operation/maintenance control signal to the operation/maintenance control signal transmitting unit  
3     550, and the operation/maintenance control signal transmitting unit 550 transmits the  
4     operation/maintenance control signal to the HACA board 442 so that the HACA board 442  
5     transmits the operation/maintenance control signal to a corresponding board.

6     **[0093]**     FIG. 6 is a configuration diagram of the WSM of FIG. 4.

7     **[0094]**     Referring to the drawing, the WSM 450 includes a general function module 610 for  
8     operating the WSM 450 itself and providing an external interface function, an operation function  
9     module 620 for providing an operational function for the pBSC and pBTS, such as loading,  
10    configuration management and statistics measurement, a maintenance function module 630 for  
11    providing a maintenance function for the pBSC and the pBTS, such as status monitoring, failure  
12    control and system tests, and an additional function module 640.

13    **[0095]**     The general function module 610 includes a WSM initialization manager (BIM) 614 for  
14    creating and managing application parts required for the operation of the WSM 450, a LAN  
15    interface manager (LIM) 612 for processing LAN connection and data transmission and reception  
16    with the system, and a User interface manager (UIM) 616 for providing a graphic user matching  
17    function.

18    **[0096]**     The operation function module 620 includes a system loading manager (SLM) 622 for  
19    handling system loading, a configuration data manager (CDM) 624 for handling configuration  
20    management, and a statistics and measurement manager (SMM) 626 for handling a statistics and  
21    measurement function.

1     **[0097]**     The maintenance function module 630 includes a status manager (STM) 632 for  
2     monitoring the status of the processors of the system, various links and various devices, a fault  
3     manager (FLM) 634 for collecting the various failures and alarms of the system and reporting them  
4     to the operator, and a test manager (TSM) 636 for testing various devices and processing test calls.

5     **[0098]**     The additional function module 640 includes a connection and communication manager  
6     642 for controlling connections, and a sanity manager (SAM) for processing sanity data created  
7     in the pBSC, the pBTS and the WSM 450.

8     **[0099]**     The WSM 450 creates and manages modules required at the time of operating itself using  
9     the BIM 614, receives operation information and maintenance information, transmitted from the  
10    BHPA board for a BMP 441 through the Fast Ethernet link, through the LIM 612, and transmits  
11    the operation information to a corresponding module 622, 624 or 626 of the operation function  
12    module 620, and transmits the maintenance information to a corresponding module 632, 634 or  
13    636 of the maintenance function module 630.

14   **[0100]**    The general function module 610 of the WSM 450 allows the operation control signal  
15    to be transmitted to the BHPA board for a BMP 441 of the pBSC by receiving the operation  
16    control signal transmitted to the BHPA board for a BMP 441 from the respective modules 622, 624  
17    and 626 of the operation function module 620, and by transmitting the operation control signal on  
18    the Fast Ethernet link using the LIM 612.

19   **[0101]**    Additionally, the general function module 610 of the WSM 450 allows the maintenance  
20    control signal to be transmitted to the BHPA board for a BMP 441 of the pBSC by receiving the  
21    maintenance control signal transmitted to the BHPA board for a BMP 441 from the respective

modules 632, 634 and 636 of the maintenance function module 630, and by transmitting the maintenance control signal on the Fast Ethernet link using the LIM 612.

**[0102]** FIG. 7 is a flowchart showing processing of the operation/maintenance information in the private mobile communication service system using the LAN in accordance with an embodiment of the present invention.

**[0103]** The HACA board 442 collects the operation/maintenance information of the respective boards, and transmits the collected operation/maintenance information to the BHPA board for a BMP 441 at step S110.

**[0104]** Thereafter, the BHPA board for a BMP 441 stores the operation/maintenance information in the memory at step S112.

**[0105]** Then, the BHPA board for a BMP 441 ascertains a link address to which the operation/maintenance information is transmitted at step S114, determines whether the operation/maintenance information is used for the WSM 450 at step S116, transmits the operation/maintenance information to the ATM network at step S118 if the operation/maintenance information is not used for the WSM 450, and transmits the operation/maintenance information to the WSM 450 at step S120 if the operation/maintenance information is used for the WSM 450.

**[0106]** Thereafter, after the general function module 610 of the WSM 450 receives the operation/maintenance information using the LAN interface module 612, the general function module 610 transmits the operation information to the operation function module 620 and the maintenance information to the maintenance function module 630 at step S122 so that a corresponding function module processes data at step S124.

1   **[0107]** FIG. 8 is a flowchart showing the processing of the operation/maintenance control signal  
2   in the private mobile communication service system using the LAN in accordance with an  
3   embodiment of the present invention.

4   **[0108]**       First, the corresponding function module of the WSM 450 creates the  
5   operation/maintenance control signal at step S210, and the corresponding function module  
6   transmits the operation/maintenance control signal to a LAN interface at step S212.

7   **[0109]**   Thereafter, the LAN interface transmits the operation/maintenance control signal to the  
8   LAN interface 530 of the BHPA board for a BMP 441 through the LAN at step S214.

9   **[0110]**   The BHPA board for a BMP 441 receives the operation/maintenance control signal  
10   through the LAN interface 530, stores the operation/maintenance control signal in the memory 560  
11   at step S216, and transmits the operation/maintenance control signal to the HACA board 442 at  
12   step S218.

13   **[0111]**   The HACA board 442 transmits the operation/maintenance control signal to a  
14   corresponding board so that proper operation/maintenance is performed at step S220.

15   **[0112]**   Meanwhile, although Fast Ethernet has been described as being an example of the LAN,  
16   the LAN is not limited to Fast Ethernet, but various types of LANs may be employed in the present  
17   invention.

18   **[0113]**   As described above, the present invention provides an apparatus and method for  
19   operating and maintaining a private mobile communication service system, in which a LAN is used  
20   as a network interface between a WSM 450 and a BMP so that it is not necessary to mount an  
21   AS1A and an STIM on a rack of a pBSC, thus providing a great cost reduction.



1     **[0114]**     Additionally, in accordance with the present invention, the WSM 450 and the BMP are  
2     connected to each other by the LAN so that they can be connected to each other using the IP  
3     network without the limitation of distance.

4     **[0115]**     Although preferred embodiments of the present invention have been disclosed for  
5     illustrative purposes, those skilled in the art will appreciate that various modifications, additions  
6     and substitutions are possible without departing from the scope and spirit of the invention, as  
7     described in the accompanying claims.